

# SUPERWINCH



# 10

## 10000 lb (44.4 KN) 12V 4WD Winch

Engineered & Designed USA

PLANETARY 3 Stage 12 volt DC

1ST LAYER 10000 lbs (44.4KN)

5.5 HP (4.1 kW) 12 volt MOTOR

FAST LINE SPEED

SUITABLE FOR STEEL OR SYNTHETIC ROPE

WATERPROOF IP68

RELOCATABLE CONTROL BOX WITH WIRING



### SX10 Specification

Power in Watts	4.1 kW (5.5hp)
Maximum Current	350 Amps
Lubrication	Synthetic Grease
Gearbox	3 Stage Planetary
Gear Ratio	218 : 1
Brake	Full Load Automatic
Remote Control	Wireless & 3.6 M corded
Free spool	Multi position Pull & Turn
Drum	63.5mm Ø x 222 mm
Weight (synthetic)	27 kg (no packaging)
Synthetic rope	3/8"(9.5mm) x 80' (25 M)
Steel Rope	3/8"(9.5mm) x 85' (26 M)

### SX10 Performance

Lbs / kgPull	Amps	Speed 1St Later
0		8.3 M p/m (27 F p/m)
2000 / 907	149	3.6 M p/m (11.9 F p/m)
4000 / 1814	228	3 M p/m (9.7 F p/m)
6000 / 2722	246	2.3 M p/m (7.5 F p/m)
8000 / 3629	331	1.9 M p/m (6.3 F p/m)
10000 / 4536	350	1.4 M p/m (4.5 F p/m)

